

SINCE 1978



LEADING LIGHT

Product Datasheet

vkleadinglight.gr



Lio

VK/04429/W/WW

Recessed ceiling light led, 5W, 2700K, 612lm, 30°, CRI>90, IP20, ø4.2cm, white



IP20    

Dimensions	Gallery	Downloads																																																																																				
 ø4.2cm 6.2cm Cut hole ø3.5cm 6.2cm	 Recessed Dark downlights Led Lio  Recessed <table><tr><th colspan="12">RECESSED</th></tr><tr><th>Model</th><th>Power</th><th>Beam angle</th><th>Light output</th><th>Color temperature</th><th>Color rendering index</th><th>IP</th><th>Material</th><th>Finish</th><th>Weight</th><th>Height</th><th>Diameter</th></tr><tr><td>VK/04429/W/WW</td><td>5W</td><td>30°</td><td>612lm</td><td>2700K</td><td>>90</td><td>IP20</td><td>Aluminum</td><td>White</td><td>12g</td><td>6.2cm</td><td>4.2cm</td></tr><tr><td>VK/04429/W/WW</td><td>5W</td><td>30°</td><td>612lm</td><td>2700K</td><td>>90</td><td>IP20</td><td>Aluminum</td><td>White</td><td>12g</td><td>6.2cm</td><td>4.2cm</td></tr><tr><td>VK/04429/W/WW</td><td>5W</td><td>30°</td><td>612lm</td><td>2700K</td><td>>90</td><td>IP20</td><td>Aluminum</td><td>White</td><td>12g</td><td>6.2cm</td><td>4.2cm</td></tr><tr><td>VK/04429/W/WW</td><td>5W</td><td>30°</td><td>612lm</td><td>2700K</td><td>>90</td><td>IP20</td><td>Aluminum</td><td>White</td><td>12g</td><td>6.2cm</td><td>4.2cm</td></tr><tr><td>VK/04429/W/WW</td><td>5W</td><td>30°</td><td>612lm</td><td>2700K</td><td>>90</td><td>IP20</td><td>Aluminum</td><td>White</td><td>12g</td><td>6.2cm</td><td>4.2cm</td></tr></table> 12	RECESSED												Model	Power	Beam angle	Light output	Color temperature	Color rendering index	IP	Material	Finish	Weight	Height	Diameter	VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm	VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm	VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm	VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm	VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm	
RECESSED																																																																																						
Model	Power	Beam angle	Light output	Color temperature	Color rendering index	IP	Material	Finish	Weight	Height	Diameter																																																																											
VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm																																																																											
VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm																																																																											
VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm																																																																											
VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm																																																																											
VK/04429/W/WW	5W	30°	612lm	2700K	>90	IP20	Aluminum	White	12g	6.2cm	4.2cm																																																																											

Technical Specifications	
Kelvin	2700K
Power	5W
Voltage	200-260V
Fitting	Recessed dark ceiling
Type	Downlight LED
Safety class	
Light source	Bridgelux COB
IP Rating	IP20
CRI	CRI>90
Dimmable	
Lifetime	20.000hrs
Driver	Built-in DC 30-45V 150mA
Working temperature	< 45°C
PAGE	214 Technical 2024
NICKNAME	Lio

Physical Specifications	
Recessed ceiling	Yes
Color	White sand
Material	Aluminium
Width	ø4.2cm
Length	ø4.2cm
Height	6.2cm
Net weight of product (kg)	0.10
Gross weight with inner box (kg)	0.13
Gross weight with master box (kg)	4.29
Cut out	ø3.5cm H6.2cm (the cut hole also fits the light driver)

Illumination Data	
Lumen	612lm
Beam angle	30°
Lighting direction	
Dark light	Yes

Packing Info	
Pcs/carton	30pcs

Certification & Warranty	
Guarantee	3 years

Energy Label



VK LEADING LIGHT
VK/04429/W/WW

A

B

C

D

E

F

G

F

5
kWh/1000h



2019/2015